Canadian Krown Dealers Inc. 35 Magnum Dr. Schomberg, Ontario, L0G 1T0 Canada (905)939-8750 / 1(800)267-5744

CODE: KR-002026

PRODUCT: Mack Corrosion Inhibitor and Lubricant - 400 g

**SECTION 01: IDENTIFICATION** 

Product Item Numbers..... KR-002026

Product Identity..... Mack Corrosion Inhibitor and Lubricant - 400 g

Manufacturer..... Empack Spraytech Inc.

98 Walker Drive Brampton Ontario

Canada L6T 4H6 905-792-6571

24 hour emergency telephone number..... In Canada: Call CANUTEC (613) 996-6666 - In The United States: Call CHEMTREC (800)

424-9300.

Recommended Use..... Lubricant, Penetrant, Rust Inhibitor.

Chemical Family..... Mixture

# **SECTION 02: HAZARD IDENTIFICATION**



Label Elements:

and delayed

Signal Word..... DANGER.

Hazard Classification:

Physical Hazards..... Flammable Aerosols - Category 1. Gases Under Pressure - Liquefied Gas .

Health Hazards..... Not Classified. Environmental Hazards..... Not Classified.

H222:Extremely flammable aerosol (1). H229:Pressurized container: may burst if heated Hazard Statement.....

(1). H280:Contains gas under pressure; may explode if heated (L).

Precautionary Statements:

P210:Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Prevention..... No smoking. P211:Do not spray on an open flame or other ignition source. P251:Do not

pierce or burn, even after use.

None Response.....

P410+P412:Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F. Storage.....

P403:Store in a well ventilated place.

Disposal..... P501:Dispose of contents/container in accordance with local, regional, national, and/or

international regulations.

Hazard(s) not otherwise classified (HNOC) None Known.

Classified according to:..... Canada's Hazardous Products Act/Hazardous Products Regulations (WHMIS 2015) and

Occupational Safety and Health Administration (OSHA).

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS						
HAZARDOUS INGREDIENTS	CAS#	WT. %				
Isobutane Propane	75-28-5 74-98-6	10-30 7-13				

## **SECTION 04: FIRST-AID MEASURES**

If inhaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.

Immediately flush the contaminated skin with soap and water. If this chemical penetrates Skin Contact..... clothing, immediately remove the clothing and flush the skin with water. If irritation persists

after washing, get medical attention.

Eye Contact..... Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs.

If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. Most important symptoms/effects, acute ...



# PRODUCT: Mack Corrosion Inhibitor and Lubricant - 400 g

# **SECTION 04: FIRST-AID MEASURES**

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**CODE: KR-002026** 

## **SECTION 05: FIRE-FIGHTING MEASURES**

Specific Hazards Arising from the Chemical In case of fire, the following can be released: Carbon Oxides (CO, CO2), Other unidentified

Organic Compounds.

Special Protective Equipment and ......

Precautions for Firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with water to prevent vapor pressure build up. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from immediate hazard area if it is safe to do.

General Fire Hazards..... Extremely flammable.

### **SECTION 06: ACCIDENTAL RELEASE MEASURES**

Personal Precautions, Protective ...... Equipment and Emergency Procedures No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid walking through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 08).

Methods and Materials for Containment  $\ldots$  and Cleaning Up

Environmental Precautions.....

Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

#### SECTION 07: HANDLING AND STORAGE

Wash with plenty of water.

Precautions for Safe Handling.....

Form

Avoid breathing vapours or mists. Never pierce, drill, grind, cut, saw or weld any empty container. Do not eat or drink while working. See Section 08 for Protective Personal Equipments.

Conditions for Safe Storage including any Incompatibilities

Keep container tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, and flame. Do not store in direct sunlight.

# SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

INGREDIENTS	TWA	CGIH TLV STEL	OSH/ PEL	A PEL STEL	NIOSH REL
Isobutane	Not available	1,000 ppm	Not available	Not available	Not available
Propane	Not available	Not available	1,000 ppm	Not available	Not available
Value if unprof showers are a Individual Protection Measures: Eye/Face Protection		Value if unprotected personshowers are available.  Chemical splash goggles Use appropriate protective None known.  None Known.  When using, do not eat, do such as washing after har	ventilation required to maintain the point of use below the Threshold Limit tected personnel are involved. Ensure that eyewash stations and safety available.  Is high goggles are recommended. It is protective clothing to avoid skin contact if required.  Id not eat, drink or smoke. Always observe good personal hygiene measures, ing after handling the material and before eating, drinking, and/or smoking. It is work clothing and protective equipment prior to use.		

### **SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES**

I UIIII	ACIU3UI.
Physical Appearance	Light Brown.
Odor	N/A.
Odor Threshold (ppm)	N/A.
Specific Gravity (Liquid)	0.835-0.875.
Specific Gravity (Aerosol)	0.761-0.791.
Vapour Density (Air=1)	N/A.
Aerosol Vapour Pressure (psig, 21°C)	70-80.
pH	N/A.
Boiling Point (Propellant), ° C	-31.61 to -11.72.
Melting / Freezing point (°C), liquid	-20.



Powered by

Aerosol



**CODE: KR-002026** 

# PRODUCT: Mack Corrosion Inhibitor and Lubricant - 400 g

# SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

-104 °C (-156°F). Estimated. (Propellant). Flash Point (°C), Method.....

Flashback..... N/A. Evaporation Rate (n-Butyl Acetate = 1)..... N/A. VOC Content.....

Solubility in water..... Insoluble.

460°C (860°F). (Isobutane).

Auto Ignition Temperature (°C)...... Lower Flammable Limit (% Vol)...... Upper Flammable Limit (% Vol)..... 1.8. (Propellant). 9.5. (Propellant).

Coefficient of Water/Oil Distribution...... N/A.

Viscosity..... 100 MPa-s. (Liquid).

## **SECTION 10: STABILITY AND REACTIVITY**

No hazardous reactions.

Chemical Stability..... Stable under the recommended storage and handling conditions.

Possibility of Hazardous Reactions..... It may catch fire on contact with oxidizing mineral acids.

Conditions to Avoid..... Heat, flames, sparks.

Incompatible Materials..... None known.

Hazardous Decomposition Products...... In combustion emits toxic fumes.

## SECTION 11: TOXICOLOGICAL INFORMATION

**INGREDIENTS** LC50 LD50

658 mg/L (Rat - 4hrs) Not available Isobutane 658 mg/L (Rat - 4hrs) Propane Not available

Information on Likely Routes of Exposure:

Routes of entry - Inhalation..... Yes. Routes of entry - Skin & Eye..... No. Symptoms Related to the Physical,

Chemical and Toxicological Characteristics Acute Toxicity..... N/A.

Skin Corrosion/Irritation..... Serious Eye Damage/Eye Irritation..... May cause mild skin irritation. May irritate eyes.

Respiratory or Skin Sensitization..... N/A.

Germ Cell Mutagenicity..... No data available to indicate product or any components present at greater than 0.1% are

mutagenic.

Carcinogenicity..... N/A.

Reproductive Toxicity..... Based on available data, the classification criteria are not met. STOT - Single Exposure..... No data available. STOT - Repeated Exposure..... No data available. Aspiration Hazard..... No data available.

Chronic Effects..... No known adverse effects.

#### SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity..... May be dangerous for the environment. No data is available on the product itself. Should

not be released into the environment. Persistence and degradability ..... The product itself has not been tested. Bioaccumulation Potential..... The product itself has not been tested. Mobility in Soil..... The product itself has not been tested.

Other Adverse Effects..... None Known.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

Appropriate Disposal Methods..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Spilled material and water rinses are classified as chemical waste and must be disposed of in accordance with current local, provincial and federal regulations.

# **SECTION 14: TRANSPORT INFORMATION**

UN1950, AEROSOLS, Class 2.1. TDG (Canada- Road).....



# PRODUCT: Mack Corrosion Inhibitor and Lubricant - 400 g

# **SECTION 15: REGULATORY INFORMATION**

Canada Regulations: V. Canadian Environmental Protection Act ... A (CEPA) US Regulations. E

WHMIS Classification. A: Compressed gas. B5: Flammable aerosol. All ingredients listed appear on the Domestic Substances List (DSL).

Environmental Protection Act: Constituents of this product are included on the TSCA inventory. This product is considered hazardous under the OSHA Hazard Communication Standard.

**CODE: KR-002026** 

### **SECTION 16: OTHER INFORMATION**

1976-USA; PEL: Permissible Exposure Limit; REL: Recommended Exposure Limit; TLV: Threshold Limit Value; VOC: Volatile Organic Content; WHMIS: Workplace Hazardous

Materials Information System STOT: Specific Target Organ Toxicity.

Prepared by ...... Regulatory Affairs Latest Revision ..... OCT 04/2018